

Alba

MANUFACTURING, INC.

CHAIN DRIVEN LIVE ROLLER CONVEYOR

Standard Features:

- ***Welded, Structural Steel Frame Construction***
- ***Drives Sized to Match Loads by Factory***
- ***230-460/3/60 Electrical Connection***
- ***High Side, Low Side and Underslung Drive Mounting***
- ***30, 45 and 60 FPM Fixed Conveyor Speed***
- ***Continuously Welded Sprockets***
- ***Rollers Set High or Low on Non-driven Side***
- ***Scalloped Type Roller Chain Guard #10 Ga. and #16 Ga. Drive Chain Guard***
- ***Heavy Duty Channel Supports +/- 3/4" Adjustment***
- ***Painted Alba Blue with Safety Yellow Guards***
- ***Units Typically Shipped Fully Assembled to Minimize Installation Time.***
- ***Conveyors Fully Tested Prior to Shipment***



Optional Items:

- ***Tread Plates***
- ***Polyurethane Roller Covering***
- ***UHMW Roller Sleeves***
- ***Zinc Plated & Zinc Flo Coated Rollers***
- ***Blade Stops/Pin Stops***
- ***Photo Eyes***
- ***Pre- Wired Devices***
- ***Back Stops/Conveyor Guides***
- ***Fork Truck Barriers***
- ***Transition Rollers***
- ***VFD Rated Motors***
- ***Hot Dipped Galvanized Frames***
- ***Color Match Paint to Specifications***
- ***Zero Pressure Accumulation Controls***



MOVE IT
on Conveyors by ●●●

Alba

MANUFACTURING, INC.

Chain Driven Live Roller Conveyor

Roller Size	Chain	Centers	Axles	Effective Widths	Lengths
1.9" Dia. x 12 Ga	RC-40 Chain	2 -1/8" DBS	7/16" Hex Axle Spring Retained	Up to 52"	4'-11" & 9'-10-1/2"
1.9" Dia. x 9 Ga		2-3/4"			4'-11" & 9'-11-1/2"
		4"			5'-0" & 10'-0"
		6"			
2-1/2" Dia. x 11 Ga	RC-40 Chain	2.75"	11/16" Hex Axle Spring Retained	Up to 60"	4'-11" & 9'-11-1/2"
		2.75" DBS			4'-11-1/4" & 9'-9-3/4"
		3.25"			5'-0" & 10'-0"
		3.75"			
		4"			
		6"			
2-1/2" Dia. x 11 Ga	RC-60 Chain	3" DBS	11/16" Hex Axle Spring Retained	Up to 60"	5'-0" & 10'-0"
		3.75"			4'-9" & 9'-9"
		4.5"			4'-10-1/2" & 9'-9"
		6"			5'-0" & 10'-0"
		9"			
		12"			
2-9/16" Dia. x 7 Ga	RC-40 Chain	2.75"	11/16" Hex Axle Spring Retained	Up to 60"	4'-11" & 9'-11-1/2"
		2.75" DBS			4'-11-1/4" & 9'-9-3/4"
		3.25"			5'-0" & 10'-0"
		4"			
		6"			
2-9/16" Dia. x 7 Ga	RC-60 Chain	3" DBS	11/16" Hex Axle Spring Retained	Up to 60"	5' & 10'
		3.75"			4'-9" & 9'-9"
		4.5"			4'-10-1/2" & 9'-9"
		6"			5'-0" & 10'-0"
		9"			
		12"			
3-1/2" x .300 wall	RC-60 Chain	4.875"	1-1/16" Hex Axle Pin Retained	Up to 66"	4'-11-5/8" & 9'-10-1/8"
		6"			5'-0" & 10'-0"
		7.5"			5'-0" & 10'-0"
		9"			4'-6" & 9'-9"
		12"			5'-0" & 10'-0"
3-1/2" x .300 wall	RC-80 Chain	6.5"	1-1/16" Hex Axle Pin Retained	Up to 66"	4'-10-1/2" & 9'-9"
		7.5"			5'-0" & 10'-0"
		10"			
4-1/4" x .4375 wall	RC-100 Chain	8.75"	1-1/4" Hex Axle Pin Retained	Up to 102"	4'-8-7/8" & 9'-5-3/4"
		10.625"			5'-3-3/4" & 9'-8-7/8"
		11.875"			4'-11-3/8" & 9'-8-7/8"
5" x .75 wall	RC-100 Chain	9.375"	1-1/2" Hex Axle Pin Retained	Up to 102"	4'-8-1/4" & 9'-4-1/2"
		11.875"			4'-11-3/8" & 9'-10-3/4"
	RC-120 Chain	9.75"			4'-10-1/2" & 9'-9"
		12.75"			5'-3-3/4" & 10'-7-1/2"

MOVE IT
on Conveyors by ●●●



MANUFACTURING, INC.

8950 Seward Road, Fairfield, Ohio 45011

Phone: (866) 252-2634 Fax: (513) 874-9476

Web: WWW.ALBAMFG.COM